



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 031/06b

DuraBlend™ Diesel Motor Oil SAE 10W-40

Premium synthetic blend passenger car motor oil -- Specially developed for turbo-diesel engines -- Exceeds most diesel manufacturer requirements.

Approvals/Performance levels

SAE 10W-40
API: CF
ACEA: A3/B4-10
MB 229.1
VW 505.00

Applications

Specially developed for turbo-diesel engines of passenger cars and light trucks.

Can be used for modern passenger cars with multi-valve technology and catalytic converter.

Suitable for direct injected diesel engines with and without turbo.

For cars operating in cold conditions.

Features and Benefits

Wear protection

Oil flows quickly even at very low temperatures. Turbo deposits are reduced to a minimum, which extends the turbo's useful life.

Engine cleanliness

Enhanced additives combat deposits, reducing friction for frequently used turbo- diesel engines.

Fuel economy

A clean diesel engine gives the best combustion and decreased fuel consumption

Breakdown resistance

Thermal and oxidation-stable oil film resists breakdown.

Multi-purpose use

Suitable for variety of cars, vans with diesel engines.



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

DuraBlend Diesel motor oil	
SAE Viscosity Grade	10W-40
Viscosity, mm²/s @ 100 °C. ASTM D-445	14.1
Viscosity, mm²/s @ 40 °C. ASTM D-445	95
Viscosity Index ASTM D-2270	152
Viscosity, mPa.s -25°C. ASTM D-5293	<7000
TBN, mg KOH/g ASTM D-2896	10.1
Pour Point, °C ASTM D-5950	-36
Specific Gravity @ 15.6°C. ASTM D-4052	0.875
Flash Point, COC, °C. ASTM D-92	225

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 031/05b

**This information only applies to products manufactured in the following location(s):
Europe**

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2014, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.