



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants - Engine Oil - Passenger Car Motor Oils

Version: 045/06b

Valvoline™ All Climate SAE 15W-40

High performance engine oil – Uniquely engineered to meet the demands of both turbo-diesel and petrol engines

All Climate SAE 15W-40 helps resist oxidation and prevent sludge formation on turbocharger bearings **not only meeting but exceeding** the demands of both turbo-diesel and petrol engines.

Approvals/Performance levels

SAE 15W-40
API SL/CF
ACEA A3/B3-10
MB 229.1
Recommended by Valvoline for use in engines specifying VW 505.00 or VW 501.01
Recommended for use where Fiat 9.55535.D2 is specified.

Applications

High performance engine oil formulated to protect turbo and non-turbocharged diesel, petrol and LPG engines.

Exceeds the severe ACEA A3/B3 limits for piston cleanliness in the Volkswagen TDI engine test

For use in passenger cars, light trucks, garden equipment, pleasure boats, motorcycles without wet clutch, etc.

Also suitable for industrial equipment such as telehandlers or forklifts.

Features and Benefits

Multi-Purpose use

Suitable for many cars, vans and other equipment operating in all conditions.

Cold starts

Multigrade engine oil guarantees an improved cold start, also in winter times.

Increased engine protection

Strong oil film protects the engine against wear and corrosion.

Engine cleanliness

Advanced detergent additives keep the engine clean and in good condition. Prevents black sludge.

Deposit control

Exceeds the severe ACEA A3/B3 limits for piston cleanliness in the Volkswagen TDI engine test

Breakdown resistance

Thermal and oxidation stable oil film resists oil breakdown.



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

All Climate motor oil	
SAE Viscosity Grade	15W-40
Viscosity, mm²/s @ 100 °C. ASTM D-445	14,5
Viscosity, mm²/s @ 40 °C. ASTM D-445	102
Viscosity Index ASTM D-2270	147
Viscosity, mPa.s -20°C. ASTM D-5293	<7000
TBN, mg KOH/g ASTM D-2896	8,6
Pour Point, °C ASTM D-5950	-39
Specific Gravity @ 15.6°C. ASTM D-4052	0,867
Flash Point, COC, °C. ASTM D-92	221

**This information only applies to products manufactured in the following location(s):
Europe**

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 045/05b

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2014, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.