



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants – Transmission Oils - Automotive

Version: 205/09

DuraBlend™ Gear Oil GL-5 SAE 75W-90

Premium synthetic blend gear oil for passenger cars, trucks, and buses.

EP gear oil suitable for differentials and transaxles where the manufacturer specifies a GL-5 oil.

DuraBlend Gear Oil GL-5 provides excellent protection and lubrication of the differential and the transaxle over a wide temperature range.

Approvals/Performance levels

SAE 75W-90
API GL-5

Applications

Developed for differentials and transaxles of passenger cars, vans, trucks, and buses where the manufacturer recommends a GL-5 transmission oil with a viscosity of SAE 75W-90.

Especially formulated for the lubrication of hypoid gears running at low and high speeds and with heavy and/or shocking loads.

Suitable for high speed and/or long distance driving.

Features and Benefits

Excellent protection

Excellent protection against wear and tear, also under high stress working conditions.

Advanced additives

Excellent additives protect against corrosion, oxidation, foaming, and deposits.

Breakdown resistance

Synthetic blend base oils and a highly balanced additive system avoid breakdowns even after long-time use.

Consistent, stable viscosity

Excellent viscosity-temperature properties even at very low temperatures. Highly stable viscosity with long-term multigrade advantages.

Fuel economy properties

Smoother lubrication contributes to better fuel economy. Increased oil circulation gives better cooling resulting in fuel savings.



Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Safety Data Sheet (SDS) is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

DuraBlend Gear Oil GL-5	
SAE Viscosity Grade	75W-90
Viscosity, mm²/s @ 100 °C. ASTM D-445	16,7
Viscosity, mm²/s @ 100 °C. After shearing(CEC: L-45-T-93).	Stay-in-grade
Viscosity, mm²/s @ 40 °C. ASTM D-445	103
Viscosity Index ASTM D-2270	175
Viscosity, mPa.s -40°C. ASTM D-2983	<150.000
Pour Point, °C ASTM D-5950	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,876
Flash Point, COC, °C. ASTM D-92	>210

Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Author:

AdG

Replaces – 205/08

**This information only applies to products manufactured in the following location(s):
Europe**

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2014, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.