

LUKOIL PANZER OIL 10W

single grade motor oil for military application

APPROVALS

MEETS REQUIREMENTS

API CD/SF
 AWT TL 9150/9-3
 MIL-L-2104C/D/F, MIL-L-46152 B/C

PRODUCT DESCRIPTION

LUKOIL PANZER OIL 10W is a high-quality, universal single grade motor oil for military application.

LUKOIL PANZER OIL 10W characterized by excellent resistance to aging, high cleaning power for combustion residues and dirt and prevents the cold sludge formation.

LUKOIL PANZER OIL 10W offers a very high wear and corrosion protection. Due to the high quality base oils without additional Additivierung natural multigrade character and very good low temperature properties.

APPLICATION

LUKOIL PANZER OIL 10W is mainly used in severely stressed, turbocharged diesel and petrol engines and for special applications according to the manufacturer's instructions using.

LUKOIL PANZER OIL 10W is also successfully used for the lubrication of gearboxes, retarders, intarders, torque converters and hydraulic systems of agricultural and construction equipment and as well as for some types of compressors.

TYPICAL TEST DATA

PROPERTY	Units	Test methods	LUKOIL PANZER OIL 10W
Density at 15 °C	kg/m ³	DIN 51757	858
Flash Point COC	°C	ISO 2592	230
Viscosity class	SAE		10W
Viscosity at 40°C	mm ² /s	DIN 51562/T1	44
Viscosity at 100°C	mm ² /s	DIN 51562/T1	7,1
Viscosity index	---	DIN ISO 2909	115
Pourpoint	°C	DIN ISO 3016	<-33

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO "LLK-International"