

LUKOIL TRANSMISSION SYNTH MPV 75W-80

Product number: 583100

Fully synthetic, fuel-efficient gearbox transmission oil

APPROVALS

Volvo 97307
MAN 341 Typ Z4
ZF TE-ML 01L, 02L, 16K (ZF003412)

MEETS REQUIREMENTS

API GL-4
DAF
EATON Transmission
IVECO 18-1807 Classe MGS1
MAN 341 Typ E3
Renault
VOITH Oil class C
VOLVO 97305, 97307
ZF TE-ML 02D, 07A, 08

PRODUCT DESCRIPTION

LUKOIL TRANSMISSION SYNTH MPV 75W-80 fully synthetic, fuel-efficient gearbox transmission oil developed specifically for commercial vehicles with extremely long oil change intervals.

LUKOIL TRANSMISSION SYNTH MPV 75W-80 shows excellent aging stability and thus is suitable for longest oil drain intervals especially for commercial vehicles. Modern high performance anti-wear and anti-corrosion additives provide a stable lubricant film and thus longest service life for transmissions. The low viscosity and outstanding cold operation properties lead to superior gear shift comfort.

APPLICATION

LUKOIL TRANSMISSION SYNTH MPV 75W-80 is best suitable for the requirements in heavy duty vehicles, busses and coaches with or without interarder. It is recommended for longest oil drain intervals. Please consider always the OEM's instruction manual!

09. Jun. 2021, Page 1/1

* This document supersedes all previous versions

Further information can be obtained from Technical Marketing Service technics.lubes@eu.lukoil.com.

TYPICAL TEST DATA

Property	Units	Test method	LUKOIL TRANSMISSION SYNTH MPV 75W-80
Density @ 15°C	kg/m ³	DIN 51757	862
Flash Point COC	°C	ISO 2592	220
Viscosity class	---	SAE J 306	75W-80
Viscosity @ 40°C	mm ² /s	DIN 51562/T1	65
Viscosity @ 100°C	mm ² /s	DIN 51562/T1	10,3
Viscosity index	---		146
Pourpoint	°C	DIN ISO 3016	<-51

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved by LUKOIL Lubricants Europe GmbH

SHELF LIFE AND STORAGE

When stored in the original unopened containers in a dry place, this product has a shelf life of at least 60 months from the date of production.

SAFETY, HEALTH, ENVIRONMENT

This product doesn't contain any toxic ingredients. During storage, transportation and application of this product, the safety rules for handling mineral lubricating materials and the environment protection regulations must be observed.

For further information on how to use LUKOIL products, please refer to the material safety data sheet:

<http://www.lukoil-lubricants.eu/>