



eni i-Base 15W-40

eni i-Base 15W-40 is an engine lubricant formulated with high quality base oils, suitable for gasoline and diesel engines that equip passenger cars or light vans operating under the severest conditions involving, for example: motorway driving or taxi service in urban traffic (stop-go service).

CHARACTERISTICS (TYPICAL FIGURES)

SAE Grade		15W-40
Density at 15 °C	kg/m ³	878
Viscosity at 100 °C	mm ² /s	14.5
Viscosity at 40 °C	mm ² /s	109
Viscosity at -20 °C	mPa·s	6800
Viscosity Index	-	130
Flash Point	°C	210
Pour Point	°C	-24

PROPERTIES AND PERFORMANCE

- **eni i-Base 15W-40** has an extremely high Viscosity Index which keeps it free-flowing when cold and maintains high viscosity when hot.
- Its superior detergent and dispersant properties effectively inhibit the formation of lacquer, varnish, sludge and other deposits, maintaining in a good condition the engine components.
- Its anti-wear properties ensure long life for all moving parts, substantially reducing the need for engine servicing and overhauls.

INTERNATIONAL SPECIFICATIONS AND APPROVALS

- ACEA A3/B4-10
- API SM/CF
- MB 229.1
- VW 501 01, 505 00 quality