



eni Rotra MP

eni Rotra MP is an **EP** (Extreme Pressure) gear oil recommended for hypoid gears operating under severe conditions and for very highly loaded gears in general, especially those subjected to dynamic loads.

It can also be used in conventional gear-boxes on cars and trucks, and in gear-boxes, final drives and power take-offs on farm and earth-moving machineries.

It can thus be used for lubricating all gears for which the manufacturer recommends an API GL-5 performance.

CHARACTERISTICS (TYPICAL FIGURES)

SAE Grade		80W-90	85W-140
Density at 15°C	kg/m ³	900	910
Viscosity at 100°C	mm ² /s	14,5	28
Viscosity at 40°C	mm ² /s	144	416
Viscosity at -12°C	mPa.s	-	120000
Viscosity at -26°C	mPa.s	120000	-
Viscosity Index	-	105	100
Flash Point COC	°C	200	205
Pour Point	°C	-30	-18

PROPERTIES AND PERFORMANCE

- Its superior EP additives ensure a continuous lubricant film even on gears operating under the severest conditions involving heavy dynamic and shock loads, and very high, or intermittent sliding speeds between the teeth.
- Its outstanding antiwear properties and its oiliness, markedly reduce gear-tooth and bearing wear.
- Its particularly good oxidation stability prevents any deterioration even when in contact with components operating at high temperatures. Thus any tendency for viscosity to increase or for sludge to form is inhibited. **eni Rotra MP** can therefore be kept in use for the long oil-service periods specified by car manufacturers.
- **eni Rotra MP** is noncorrosive to steel, copper and other metals and alloys, and thus helps keep lubricated parts in first-class condition.
- Its antirust properties effectively prevent rust on gears and in bearings even when moisture is present.
- Its antifoam qualities minimize the formation of air bubbles which could adversely affect lubricant film continuity.



eni Rotra MP

SPECIFICATIONS

eni Rotra MP is officially approved by or meets the requirements of the following service and specifications:

API GL-5
MIL-L-2105D
MAN 342 Typ M1 (SAE 80W-90)
ZF TE-ML 16D, 21A (SAE 85W-140)
ZF TE-ML 16B, 17B, 19B, 21A (SAE 80W-90)
Volkswagen TL 727/726
Volvo 97310/97313/97314
Ford M2C-105A
Ford M2C-154A
Ford SQM-2C-9002A/9008A/9101A
Chrysler MS-5644
General Motors MS 9985290
Opel B 0401010
LIEBHERR