



RAVENOL MARINE Gear Lube

RAVENOL MARINE Gear Lube contains high-quality base oils, with a balanced combination of additives. This guarantees a high load carrying capacity, wear protection and oxidation stability.

Because of the balanced additive combination good viscosity-temperature behavior, low pour point and suppression of foam formation allows use with different operating conditions.

Application Notes

RAVENOL MARINE Gear Lube is gear oil for lubricating when GL-5 transmission types are required.

Quality Classifications

Specifications

API GL-5

Practice and tested in aggregates with filling

OMC, VOLVO PENTA, Mercruiser, YANMAR

Characteristic

RAVENOL MARINE Gear Lube offers:

- Good adhesion and pressure-resistant lubricating film
- Excellent oxidation stability
- Very good viscosity-temperature behaviour
- Wear-resistant effect
- No foaming tendency
- A neutral behaviour towards metals and sealing materials

| Characteristics | Unit | Data | Audit |
|----------------------|--------------------|---------|--------------|
| Density at 20°C | kg/m ³ | 895,0 | EN ISO 12185 |
| Colour | | blue | visual |
| Viscosity at 100°C | mm ² /s | 14,1 | DIN 51562-10 |
| Viscosity at 40°C | mm ² /s | 140,5 | DIN 51562-10 |
| Viscosity index VI | | 97 | DIN ISO 2909 |
| Brookfield Viscosity | mPa*s | 108.800 | ASTM D 2983 |
| Pourpoint | °C | -33 | DIN ISO 3016 |
| Flash point (COC) | °C | 226 | DIN ISO 2592 |
| Copper Strip Test | | 1b | ASTM D130 |

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

03.04.2018

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 052039719-40 / 41