

Optigear Synthetic RO

High performance gear oil

Description

Optigear™ Synthetic RO range are high-performance, synthetic oils developed especially for gears used in rail traffic and mechanical engineering applications (such as in Robots). The properties of Optigear Synthetic RO mean it can be used in extreme climate conditions and for long-term use.

Optigear Synthetic RO is formulated with Castrol's Microflux Trans (MFT) Plastic Deformation (PD) additive. MFT PD helps improve performance when operating temperature and loads reach a certain level of activation energy, by enabling the micro-smoothing of surface roughness without increasing wear. The smoothed surface delivers optimum wear protection and an extremely low coefficient of friction, especially in applications which experience extreme pressure, shock loads, vibrations or low speeds. MFT PD helps to protect against scuffing and shock loading, while maintaining a high load carrying capacity, and can help prevent the progression of micro-pitting in pre-damaged gears.

Application

All types of spur gear teeth, also under difficult load conditions.

Bevel gear units, including those with a large offset (hypoid) and heavy alternating loads.

All types of roller bearings, with heavy loads and low and high temperatures. Can be used in a very broad range of temperatures (no preheating needed in winter).

Dip lubrication at high numbers of revolutions, as well as injection and oil mist lubrication.

No influence on usual sealing materials or paint in gear casings.

Filtering (mechanical) does not result in any additive loss.

Not for synchronised gears or limited slip differentials due to low friction coefficients.

Advantages

- High pressure absorption and excellent wear protection¹
- Safe bearing lubrication in high- and low-temperature ranges
- High seizure load-bearing capacity¹
- Above-average application times – even under difficult conditions¹
- Reduction of friction coefficient and operating temperature¹
- Good corrosion protection¹
- Long service life for gears¹
- Exceeds requirements regarding wear protection in line with DIN 51517, part 3

¹When compared to conventional gear oils.

Typical Characteristics

Name	Method	Units	RO 32	RO 150	RO 220
Appearance	Visual	-	blue green	blue green	blue green
Density @ 15°C / 59°F	ASTM D 4052 DIN 51757	Kg/m ³	850	868	875
Viscosity, Kinematic @ 40°C / 104°F	ASTM D 445 ISO 3104	mm ² /s	32	150	200
Viscosity, Kinematic @ 100°C / 212°F	ASTM D 445 ISO 3104	mm ² /s	6.0	18.0	22.2
Viscosity Index	ASTM D 2270 ISO 2909	-	125	130	134
Pour Point	ASTM D 97 DIN-ISO 3016	°C / °F	- 45 / -49	- 45 / -49	- 45 / -49
Copper Corrosion (24hrs @ 100°C / 212°F)	ASTM D 130 DIN EN ISO 2160	-	1	1	1
Flash Point - open cup method	ASTM D 92 DIN EN ISO 2592	°C / °F	210 / 410	210 / 410	210 / 410

Subject to usual manufacturing tolerances.

Optigear Synthetic RO

31 Oct 2014

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial