



## RAVENOL Getriebeöl PSA SAE 75W-80



**VISCOSITY** 75W-80  
**SPECIFICATIONS** API GL-4  
**FABRICATION** SEMI-SYNTHETIC  
**RECOMMENDATIONS** PSA STANDARD B 71 2315

**RAVENOL GETRIEBEÖL PSA SAE 75W-80** is a high-quality solvent refined base oil based semi-synthetic multi-grade transmission oil with special EP (extreme pressure) properties.

**RAVENOL GETRIEBEÖL PSA SAE 75W-80** has a special formula for outstanding wear protection and lubrication properties.

### ART.-NR. 1222100

1 L	1222100-001
4 L	1222100-004
10 L	1222100-010
20 L	1222100-020
20 L	1222100-B20
60 L	1222100-060
60 L	1222100-D60
208 L	1222100-208
208 L	1222100-D28
1000 L	1222100-700

## Application Notes

**RAVENOL GETRIEBEÖL PSA SAE 75W-80** is used in manual shift transmissions requiring trouble-free lubrication.

**RAVENOL GETRIEBEÖL PSA SAE 75W-80** can be used in manual transmissions where the manufacturer specifies a low-viscosity oil.

## Characteristics

**RAVENOL GETRIEBEÖL PSA SAE 75W-80** offers:

- Outstanding oxidation protection
- Low viscosity in low temperatures
- Excellent wear protection
- Enhanced EP properties
- Good foaming properties
- Neutral to sealants
- Outstanding protection from rust and corrosion



Property	Unit	Data	Audit
Density at 20°C	kg/m <sup>3</sup>	843,0	EN ISO 12185
Colour		gelbbraun	visual
Viscosity at 100°C	mm <sup>2</sup> /s	8,5	DIN 51562-10
Viscosity at 40°C	mm <sup>2</sup> /s	43,1	DIN 51562-10
Viscosity index VI		178	DIN ISO 2909
Brookfield Viscosity	mPa*s	52.500	ASTM D 2983
Pourpoint	°C	-39	DIN ISO 3016
Flash point	°C	234	DIN ISO 2592
Copper Strip Test		1b	ASTM D130

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 30. April 2021